



Press&Go!

Step up your sample preparation with SEPARA® syringeless filter vials from GVS Life Sciences





SEPARA® integrates in one single device auto-sampler vial, filtration membrane, plunger, and cap/septa.

- ◆ Save money Eliminate the need for separate syringes, syringe filters, vials and septa, reducing sample preparation costs by 50%
- Save operator time 15 seconds SEPARA® Press&Go!, against 3 minutes with conventional sample preparation methods
- Speed up process with high throughput automation Designed and compatible for use with all HPLC or UHPLC auto-samplers
- Preserve precious samples Start with less sample volume; dead volume as low as 30 microliters (μL)
- Reduce risk of cross-contaminations No cumbersome steps transferring sample between different devices
- Extend column life and needle longevity Reduce risks of clogging and back pressure build up
- Increase operator security Safer single step process
- ◆ Reduce identification errors Color-coded caps by membrane type and pore size



















filtered sample ready for analysis

Technical Specifications

Dimensions – 12 mm diameter x 32 mm height **Materials** – Housing, cap: polypropylene;

septa: PTFE/silicone

Maximum Volume – 480 microliters (μL)

Dead Volume – 30 microliters (μL)

Compression Force – 8 psi (0.6 bar) approximately

Maximum Operating Temperature – 50°C (120°F)

Automation – Designed for use with all auto-

samplers and compressor units



Membrane	Properties	Compounds Class
PTFE	Hydrophobic - Chemically and biologically inert -	Organic solvents, acids, alcohols,
(Polyetetrafluoroethylene)	Superior chemical resistance	bases, aromatics
RC	Hydrophilic - Very low protein binding -	Aqueous and organic solutions
(Regenerated Cellulose)	Resistant to a wide range of solvents	
NY	Hydrophilic - Low protein binding -	Bases, HPLC solvents, alcohols,
(Nylon)	Superior strength - Resistant to organic solvents	aromatic hydrocarbons
PVDF	Hydrophilic - Very low protein binding -	Alcohols, biomolecules
(Polyvinylidene Fluoride)	High flow rates	
PES	Hydrophilic - Designed to remove particulates -	Filtration of buffers and
(Polyethersulfone)	Low protein and drug binding - High strength and durability	culture media

Ordering information

Membrane Material	Pore Size (μm)	Color	Product Code 100/pk
Polytetrafluoroethylene (PTFE)	0.20	Pink	MV32ANPPT002TC01
Polytetrafluoroethylene (PTFE)	0.45	Red	MV32ANPPT004CC01
Regenerated Cellulose (RC)	0.20	Gray	MV32ANPRC002GC01
Regenerated Cellulose (RC)	0.45	Black	MV32ANPRC004LC01
Nylon (NY)	0.20	Light Blue	MV32ANPNY002BC01
Nylon (NY)	0.45	Blue	MV32ANPNY004UC01
Polyvinylidene Fluoride (PVDF)	0.20	Yellow	MV32ANPPV002FC01
Polyvinylidene Fluoride (PVDF)	0.45	Orange	MV32ANPPV004lC01
Polyethersulfone (PES)	0.20	Light Green	MV32ANPPS002EC01
Polyethersulfone (PES)	0.45	Dark Green	MV32ANPPS004WC01